


Clutch selection guide



1
Pressure on
3 sides



2
Load
distribution



3
Line retrieval
with closed
lever



4
Emergency
opening



MODELS	CAM 611		V-GRIP*			V-CAM R814* / 814*			V-GRIP PLUS*			
	CAM 611	CAM 611 / V*	10	12	14	10	12	14	12	14	16	
LINE DIAMETER ↓		6 8										
∅ = 6 mm	250	400										
∅ = 8 mm	380		600	600		600						
∅ = 10 mm	500			700	700	850	850		1050			
∅ = 12 mm				1000	1000	1000		1200	1200	1400	1400	
∅ = 14 mm					1300	1300			1500		1700	1700
∅ = 16 mm						1600						2100

CLUTCH MAX LOAD kg

* These models are fitted with the **V-Grip system** that is internationally patented.

V-GRIP SYSTEM CLUTCHES

The V-Grip is an Antal patented system for rope locking. It works with a pressure exerted on 3 sides of the line with a higher friction and, consequently, with a lower pressure, in order not to damage manoeuvres. All Antal clutches, except the Cam 611, are fitted with the V-Grip system.

The V-Grip system has the following characteristics:

- 1 Pressure on three sides.** Unlike the usual flat cam, V-Grip is fitted with a V-shaped cam that improves the holding strength without damaging the line cover.
- 2 Load distribution.** The curved base-V-Cam pair increases the bearing surface, preventing the load from being concentrated at a critical point.
- 3 Line retrieval with closed lever.** Line retrieval can be achieved with the lever closed. The line stops automatically in the new position with no slippage.
- 4 Emergency opening.** The line can be released under load without the use of a winch because the Antal mechanism guarantees easy opening even under heavy conditions.






Ocean Tec 50

CLUTCH RANGE

A complete range with 7 different models for lines from 6 to 22 mm. All Antal models, except the Maxi, the QR and the DV-Jammer, are available in single, double, triple and quadruple versions. The Cam 611 and Cam 814 are also available in a silver version with the new ergonomic aluminium lever.

CLUTCH SELECTION

Max loads of the lower table for each model and for different line diameters have been obtained from extensive tests. Tests reveal best results on Dyneema™ with composite Kevlar/Polyester covers, while traditional pure-Polyester covers over a Dyneema™ core prove to have poor resistance. Also "all-Polyester" core/cover versions give excellent results.

MODELS														
	V-GRIP MAXI*					QR			DV JAMMERS					
LINE DIAMETER ↓	14	16	18	20	22	10	12	14 NEW	8	10	12	14	16	18
Ø = 8 mm									1500					
Ø = 10 mm						1600				2000				
Ø = 12 mm	1400						2200				3000			
Ø = 14 mm	1700	1700						3000				4000		
Ø = 16 mm		2100	2100										5000	
Ø = 18 mm			2600	2600										6000
Ø = 20 mm				3000	3000									
Ø = 22 mm					3400									